

TRU-LOCK PRODUCT APPLICATIONS GUIDE

Tru-Lock Interlocking PVC Tiles are suitable for Domestic, Commercial and Industrial applications.

To achieve the best results, it is of the utmost importance to understand the application and how best to apply the Tru-Lock floor medium to it.

THERE ARE TWO SYSTEMS THAT CAN BE CONSIDERED –

- **FREE-LAID** (No adhesives used)
- **FULLY ADHERED** (Adhered using Tru-Glu Two-part polyurethane or similar)

RULES FOR DETERMINING YOUR REQUIREMENT (To glue or not to glue?)

- 1) In some cases, where there are extreme variances in temperature or direct sunlight Tru-Lock may need to be glued down, as the intense heat will cause them to shrink or expand. We recommend using a suitable polyurethane (PU) adhesive (Tru-Glu Two-part polyurethane or similar).
- 2) Tru-Lock will withstand any underfoot traffic regardless of how high it is, taking point 1 into consideration.
- 3) Areas with heavy rolling loads and high point loading will require glue.
- 4) Tru-Lock can be installed onto any floor that are clean, level and firm.
- 5) Areas with problematic liquids (Blood, Petro-chemicals, Dairy) must be glued.

APPLICATIONS –

- Schools • Workshops • Cargo containers • Warehouses • Retail floors • Mechanical service areas
- Event floors • Offices • Goods receiving • High-impact areas • Manufacturing Floors
 - Mezzanine floors • Engineering workshops • Domestic Garages • Bottle stores
 - Sporting Change Rooms • Rented Spaces • Boarding Establishments • Equipment rooms
 - Stages • Hallways • Manufacturing areas • Mechanical service areas • Parts departments
 - Service areas • Trade show exhibits • Training facilities • Bar areas • Basements
 - Boats (enclosed areas) • Fitness areas • Commercial Kitchens • Storage areas
 - Temporary installations • Bottling Plants • Workshops • Production Lines • Safety Flooring
 - Floor Protection • Goods receiving areas • Cold Storage